

# NCV2904

/VEE LM358 LM324 3.0 V 32 V MC1741

- Short Circuit Protected Outputs
- True Differential Input Stage
- Single Supply Operation: 3.0 V to 32 V
- Low Input Bias Currents
- Internally Compensated
- Common Mode Range Extends to Negative Supply
- Single and Split Supply Operation
- ESD Clamps on the Inputs Increase Ruggedness of the Device without Affecting Operation
- Pb-Free Packages are Available

	Pricing (\$/Unit)	Compliance	Status	Rail to Rail	Channels	V <sub>S</sub> Min (V)	V <sub>S</sub> Max (V)	I <sub>D</sub> Typ (mA)	V <sub>OS</sub> Max (mV)	GBW Typ (MHz)	SR Typ (V/μs)	I <sub>O</sub> Typ (mA)	ΔV <sub>OS</sub> /ΔT (μV/C)	e <sub>N</sub> (nV/√Hz)	I <sub>bias</sub> Typ (pA)	CMRR Typ (dB)	Architecture	Temperature Range (°C)	Package Type
NCV2904DMR2G	0.1639		Active	No	2	3	32	0.75	7	1	0.6	40	7	-	-45000	70	Bipolar	-40 to 125	Mic8
NCV2904DR2G	0.0867		Active	No	2	3	32	0.75	7	1	0.6	40	7	-	-45000	70	Bipolar	-40 to 125	SOLC-8