

<b>SURFACE MOUNT GENERAL PURPOSE SILICON RECTIFIER</b>	Reverse Voltage - 50 to 1000 Volts Forward Current -1.0 Ampere																																																																																																																						
<p style="text-align: center;"><b>SOD-123FL</b></p> <p style="text-align: center; font-size: small;">Dimensions in inches and (millimeters)</p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>◆ Glass passivated device</li> <li>◆ Ideal for surface mounted applications</li> <li>◆ Low reverse leakage</li> <li>◆ Metallurgically bonded construction</li> <li>◆ High temperature soldering guaranteed: 260°C/10 seconds, 0.375" (9.5mm) lead length, 5 lbs. (2.3kg) tension</li> </ul> <p><b>Mechanical Data</b></p> <p><b>Case:</b> SOD-123FL molded plastic body over passivated chip  <b>Terminals:</b> Solderable per MIL-STD-750, Method 2026  <b>Polarity:</b> Color band denotes cathode end  <b>Mounting Position:</b> Any  <b>Weight:</b> 0.0007 ounce, 0.02 grams</p>																																																																																																																						
<b>MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS</b>																																																																																																																							
Ratings at 25°C ambient temperature unless otherwise specified. Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.																																																																																																																							
	<table border="1" style="width:100%; border-collapse: collapse; font-size: x-small;"> <thead> <tr> <th style="width:15%;">SYMBOLS</th> <th>1N4001W</th> <th>1N4002W</th> <th>1N4003W</th> <th>1N4004W</th> <th>1N4005W</th> <th>1N4006W</th> <th>1N4007W</th> <th>UNITS</th> </tr> <tr> <td></td> <th>A1</th> <th>A2</th> <th>A3</th> <th>A4</th> <th>A5</th> <th>A6</th> <th>A7</th> <td></td> </tr> </thead> <tbody> <tr> <td>Maximum repetitive peak reverse voltage</td> <td>V<sub>RRM</sub></td> <td>50</td> <td>100</td> <td>200</td> <td>400</td> <td>600</td> <td>800</td> <td>1000</td> <td>V</td> </tr> <tr> <td>Maximum RMS voltage</td> <td>V<sub>RMS</sub></td> <td>35</td> <td>70</td> <td>140</td> <td>280</td> <td>420</td> <td>560</td> <td>700</td> <td>V</td> </tr> <tr> <td>Maximum DC blocking voltage</td> <td>V<sub>DC</sub></td> <td>50</td> <td>100</td> <td>200</td> <td>400</td> <td>600</td> <td>800</td> <td>1000</td> <td>V</td> </tr> <tr> <td>Maximum average forward rectified current at T<sub>L</sub>=100°C (NOTE 1)</td> <td>I<sub(av)< sub=""></sub(av)<></td> <td colspan="6" style="text-align: center;">1.0</td> <td></td> <td>A</td> </tr> <tr> <td>Peak forward surge current 8.3ms single half sine-wave superimposed on rated load</td> <td>I<sub>FSM</sub></td> <td colspan="6" style="text-align: center;">25.0</td> <td></td> <td>A</td> </tr> <tr> <td>Maximum instantaneous forward voltage at 1.0A</td> <td>V<sub>F</sub></td> <td colspan="6" style="text-align: center;">1.1</td> <td></td> <td>V</td> </tr> <tr> <td>Maximum DC reverse current T<sub>A</sub>=25°C at rated DC blocking voltage T<sub>A</sub>=125°C</td> <td>I<sub>R</sub></td> <td colspan="6" style="text-align: center;">10.0 50.0</td> <td></td> <td>μA</td> </tr> <tr> <td>Typical junction capacitance (NOTE 2)</td> <td>C<sub>J</sub></td> <td colspan="6" style="text-align: center;">4</td> <td></td> <td>pF</td> </tr> <tr> <td>Typical thermal resistance (NOTE 3)</td> <td>R<sub>θJA</sub></td> <td colspan="6" style="text-align: center;">95</td> <td></td> <td>°C/W</td> </tr> <tr> <td>Operating junction and storage temperature range</td> <td>T<sub>J</sub>, T<sub>STG</sub></td> <td colspan="6" style="text-align: center;">-55 to +150</td> <td></td> <td>°C</td> </tr> </tbody> </table>	SYMBOLS	1N4001W	1N4002W	1N4003W	1N4004W	1N4005W	1N4006W	1N4007W	UNITS		A1	A2	A3	A4	A5	A6	A7		Maximum repetitive peak reverse voltage	V <sub>RRM</sub>	50	100	200	400	600	800	1000	V	Maximum RMS voltage	V <sub>RMS</sub>	35	70	140	280	420	560	700	V	Maximum DC blocking voltage	V <sub>DC</sub>	50	100	200	400	600	800	1000	V	Maximum average forward rectified current at T <sub>L</sub> =100°C (NOTE 1)	I <sub(av)< sub=""></sub(av)<>	1.0							A	Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	I <sub>FSM</sub>	25.0							A	Maximum instantaneous forward voltage at 1.0A	V <sub>F</sub>	1.1							V	Maximum DC reverse current T <sub>A</sub> =25°C at rated DC blocking voltage T <sub>A</sub> =125°C	I <sub>R</sub>	10.0 50.0							μA	Typical junction capacitance (NOTE 2)	C <sub>J</sub>	4							pF	Typical thermal resistance (NOTE 3)	R <sub>θJA</sub>	95							°C/W	Operating junction and storage temperature range	T <sub>J</sub> , T <sub>STG</sub>	-55 to +150							°C
SYMBOLS	1N4001W	1N4002W	1N4003W	1N4004W	1N4005W	1N4006W	1N4007W	UNITS																																																																																																															
	A1	A2	A3	A4	A5	A6	A7																																																																																																																
Maximum repetitive peak reverse voltage	V <sub>RRM</sub>	50	100	200	400	600	800	1000	V																																																																																																														
Maximum RMS voltage	V <sub>RMS</sub>	35	70	140	280	420	560	700	V																																																																																																														
Maximum DC blocking voltage	V <sub>DC</sub>	50	100	200	400	600	800	1000	V																																																																																																														
Maximum average forward rectified current at T <sub>L</sub> =100°C (NOTE 1)	I <sub(av)< sub=""></sub(av)<>	1.0							A																																																																																																														
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	I <sub>FSM</sub>	25.0							A																																																																																																														
Maximum instantaneous forward voltage at 1.0A	V <sub>F</sub>	1.1							V																																																																																																														
Maximum DC reverse current T <sub>A</sub> =25°C at rated DC blocking voltage T <sub>A</sub> =125°C	I <sub>R</sub>	10.0 50.0							μA																																																																																																														
Typical junction capacitance (NOTE 2)	C <sub>J</sub>	4							pF																																																																																																														
Typical thermal resistance (NOTE 3)	R <sub>θJA</sub>	95							°C/W																																																																																																														
Operating junction and storage temperature range	T <sub>J</sub> , T <sub>STG</sub>	-55 to +150							°C																																																																																																														
<p><b>Note:</b> 1. Averaged over any 20ms period.                  2. Measured at 1MHz and applied reverse voltage of 4.0V D.C.                  3. PCB mounted on 0.2*0.2" (5.0*5.0mm) copper pad area.</p>																																																																																																																							

**RATINGS AND CHARACTERISTIC CURVES 1N4001W THRU 1N4007W**

