



Surface Mount Schottkarrier Rectifier		Reverse Voltage - 40V Forward Current - 1.0 A																																																
<u>SOD-123FL</u>		<b>Features</b>																																																
 <table border="1" data-bbox="203 818 658 930"> <thead> <tr> <th>PIN</th><th>DESCRIPTION</th></tr> </thead> <tbody> <tr> <td>1</td><td>Cathode</td></tr> <tr> <td>2</td><td>Anode</td></tr> </tbody> </table>		PIN	DESCRIPTION	1	Cathode	2	Anode	<ul style="list-style-type: none"> <li>• Metal silicon junction, majority carrier conduction</li> <li>• For surface mounted applications</li> <li>• Low power loss, high efficiency</li> <li>• High forward surge current capability</li> <li>• For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications</li> </ul>																																										
PIN	DESCRIPTION																																																	
1	Cathode																																																	
2	Anode																																																	
<b>Mechanical Data</b> <ul style="list-style-type: none"> <li>• Case: SOD-123FL</li> <li>• Terminals: Solderable per MIL-STD-750, Method 2026</li> <li>• Approx. Weight: 15mg 0.00048oz</li> </ul>																																																		
<b>Absolute Maximum Ratings and Electrical characteristics</b> Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz resistive or inductive load, for capacitive load, derate by 20 %																																																		
<table border="1"> <thead> <tr> <th>Parameter</th><th>Symbols</th><th>MBRS140</th><th>Units</th></tr> </thead> <tbody> <tr> <td>Maximum Repetitive Peak Reverse Voltage</td><td><math>V_{RRM}</math></td><td>40</td><td>V</td></tr> <tr> <td>Maximum RMS voltage</td><td><math>V_{RMS}</math></td><td>28</td><td>V</td></tr> <tr> <td>Maximum DC Blocking Voltage</td><td><math>V_{DC}</math></td><td>40</td><td>V</td></tr> <tr> <td>Maximum Average Forward Rectified Current</td><td><math>I_{F(AV)}</math></td><td>1.0</td><td>A</td></tr> <tr> <td>Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)</td><td><math>I_{FSM}</math></td><td>30</td><td>A</td></tr> <tr> <td>Max Instantaneous Forward Voltage at 1 A</td><td><math>V_F</math></td><td>0.55</td><td>V</td></tr> <tr> <td>Maximum DC Reverse Current <math>T_a = 25^\circ C</math> at Rated DC Reverse Voltage <math>T_a = 100^\circ C</math></td><td><math>I_R</math></td><td>0.3 10</td><td>mA</td></tr> <tr> <td>Typical Junction Capacitance <sup>(1)</sup></td><td><math>C_j</math></td><td>110</td><td>pF</td></tr> <tr> <td>Typical Thermal Resistance <sup>(2)</sup></td><td><math>R_{\theta JA}</math></td><td>100</td><td>°C/W</td></tr> <tr> <td>Operating Junction Temperature Range</td><td><math>T_j</math></td><td>-55 ~ +150</td><td>°C</td></tr> <tr> <td>Storage Temperature Range</td><td><math>T_{stg}</math></td><td>-55 ~ +150</td><td>°C</td></tr> </tbody> </table>			Parameter	Symbols	MBRS140	Units	Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	40	V	Maximum RMS voltage	$V_{RMS}$	28	V	Maximum DC Blocking Voltage	$V_{DC}$	40	V	Maximum Average Forward Rectified Current	$I_{F(AV)}$	1.0	A	Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	$I_{FSM}$	30	A	Max Instantaneous Forward Voltage at 1 A	$V_F$	0.55	V	Maximum DC Reverse Current $T_a = 25^\circ C$ at Rated DC Reverse Voltage $T_a = 100^\circ C$	$I_R$	0.3 10	mA	Typical Junction Capacitance <sup>(1)</sup>	$C_j$	110	pF	Typical Thermal Resistance <sup>(2)</sup>	$R_{\theta JA}$	100	°C/W	Operating Junction Temperature Range	$T_j$	-55 ~ +150	°C	Storage Temperature Range	$T_{stg}$	-55 ~ +150	°C
Parameter	Symbols	MBRS140	Units																																															
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	40	V																																															
Maximum RMS voltage	$V_{RMS}$	28	V																																															
Maximum DC Blocking Voltage	$V_{DC}$	40	V																																															
Maximum Average Forward Rectified Current	$I_{F(AV)}$	1.0	A																																															
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	$I_{FSM}$	30	A																																															
Max Instantaneous Forward Voltage at 1 A	$V_F$	0.55	V																																															
Maximum DC Reverse Current $T_a = 25^\circ C$ at Rated DC Reverse Voltage $T_a = 100^\circ C$	$I_R$	0.3 10	mA																																															
Typical Junction Capacitance <sup>(1)</sup>	$C_j$	110	pF																																															
Typical Thermal Resistance <sup>(2)</sup>	$R_{\theta JA}$	100	°C/W																																															
Operating Junction Temperature Range	$T_j$	-55 ~ +150	°C																																															
Storage Temperature Range	$T_{stg}$	-55 ~ +150	°C																																															
(1) Measured at 1 MHz and applied reverse voltage of 4 V D.C (2) P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.																																																		


**Fig.1 Forward Current Derating Curve**




**Fig.2 Typical Reverse Characteristics**




**Fig.3 Typical Forward Characteristic**




**Fig.4 Typical Junction Capacitance**



**Fig.5 Maximum Non-Repetitive Peak Forward Surge Current**




**Fig.6- Typical Transient Thermal Impedance**



## PACKAGE OUTLINE

Plastic surface mounted package; 2 leads


SOD-123FL



UNIT		A	C	D	E	e	g	H <sub>E</sub>	∠
mm	max	1.1	0.20	2.9	1.9	1.1	0.9	3.8	7°
	min	0.9	0.12	2.6	1.7	0.8	0.7	3.5	
mil	max	43	7.9	114	75	43	35	150	7°
	min	35	4.7	102	67	31	28	138	

The recommended mounting pad size

Marking



Unit:  $\frac{\text{mm}}{(\text{mil})}$

Type number	Marking code
MBRS140	X4