



Rating:0.5A 30V DC
 Contact Resistance:100 mΩ Max.
 Operating temperature:-20℃~70℃
 Operating force:3~20N
 Operating Life:5,000cycles

ECN NO.	REV.	DATE.	DESCRIPTION.	CHECK.	APPRO.																																							
	A		NEW																																									
<table border="1"> <tr> <td>② Terminal</td> <td>8</td> <td>Phosphor bronze/kg/Au Plating</td> </tr> <tr> <td>① Housing</td> <td>1</td> <td>Nylon Black</td> </tr> <tr> <td>ITEM PART NAME</td> <td>TER'NO., QTY.</td> <td>MATERIAL FINISHING</td> </tr> <tr> <td>APPROVALS</td> <td>DATE</td> <td></td> </tr> <tr> <td>DRAWN J.X.Zhang</td> <td>2016/05/11</td> <td></td> </tr> <tr> <td>CHECKED</td> <td>TITLE:</td> <td>PHONE JACKES</td> </tr> <tr> <td>APPROVALS</td> <td>PART NO.</td> <td>PJ-393-8A</td> </tr> <tr> <td>TOLERANCES ARE</td> <td>SCALE: 1:1</td> <td>PROJ. 4</td> </tr> <tr> <td>30~0.15</td> <td>±0.30</td> <td>ANGLE</td> </tr> <tr> <td>10~0.30</td> <td>±0.20</td> <td>UNIT: mm</td> </tr> <tr> <td>5~10</td> <td>±0.15</td> <td>±2'</td> </tr> <tr> <td>~5</td> <td>±0.10</td> <td>DRAWING NO.</td> </tr> <tr> <td></td> <td></td> <td>SHEET 1 OF 1</td> </tr> </table>						② Terminal	8	Phosphor bronze/kg/Au Plating	① Housing	1	Nylon Black	ITEM PART NAME	TER'NO., QTY.	MATERIAL FINISHING	APPROVALS	DATE		DRAWN J.X.Zhang	2016/05/11		CHECKED	TITLE:	PHONE JACKES	APPROVALS	PART NO.	PJ-393-8A	TOLERANCES ARE	SCALE: 1:1	PROJ. 4	30~0.15	±0.30	ANGLE	10~0.30	±0.20	UNIT: mm	5~10	±0.15	±2'	~5	±0.10	DRAWING NO.			SHEET 1 OF 1
② Terminal	8	Phosphor bronze/kg/Au Plating																																										
① Housing	1	Nylon Black																																										
ITEM PART NAME	TER'NO., QTY.	MATERIAL FINISHING																																										
APPROVALS	DATE																																											
DRAWN J.X.Zhang	2016/05/11																																											
CHECKED	TITLE:	PHONE JACKES																																										
APPROVALS	PART NO.	PJ-393-8A																																										
TOLERANCES ARE	SCALE: 1:1	PROJ. 4																																										
30~0.15	±0.30	ANGLE																																										
10~0.30	±0.20	UNIT: mm																																										
5~10	±0.15	±2'																																										
~5	±0.10	DRAWING NO.																																										
		SHEET 1 OF 1																																										
<p>Rating:0.5A 30V DC Contact Resistance:100 mΩ Max. Operating temperature:-20℃~70℃ Operating force:3~20N Operating Life:5,000cycles</p>																																												
<p>Model NO PJ-393-8A</p>																																												
<p>Schematic</p>																																												
<p>PHONON ELECTRONICS CO.,LTD</p>																																												