



PIN NO.	PIN NAME
C 1	Supply Voltage Vcc
C 2	Reset (RST)
C 3	Clock (CLK)
C 4	N/A
C 5	Ground
C 6	Programming Voltage Vpp
C 7	I/O
C 8	N/A

- Specification:
- 1.Current rating:1.0 AMP
 - 2.Voltage rating: 12V DC
 - 3.Dielectric strength:500V AC RMS for 1 minute.
 - 4.Contact resistance:30mΩ
 - 5.Insulator resistance:500MΩ max.
 - 6.Mating un mating cycles:5000 cycles
 - 7.Packaging: 600pcs/Reel

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
③	Shell	---	1	SUS	Ni Plated	
②	Terminal	---	6	Phosphor Bronze	Sn Plated	
①	Housing	---	1	LCP	Black	

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			
<p>DRAWN JKUNLU 2014/9/29</p> <p>CHECKED</p> <p>APPROVALS</p> <p>TOLERANCES ARE 30~125 ±0.30 ANGLE PART NO. SIM-08A 10~30 ±0.25 UNIT: mm SCALE: 1:1 PROJ: 1 OF 1 5~10 ±0.20 DRAWING NO. SHEET 1 OF 1 ~5 ±0.15</p>						

