



RECOMMENDED P.C.B. PATTERN LAY OUT

NOTES:

1. HOUSING: SEE NOTES, UL94V-0.

TERMINAL: SEE NOTES.

SHELL: SEE NOTES.

SPECIFICATION:

1. ELECTRICAL CHARACTERISTIC:

CONTACT RESISTANCE: 30MΩ MAX

DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1MIN

INSULATION RESISTANCE: 1000MΩ MIN

2. MECHANICAL CHARACTERISTIC:

INSERTION FORCE: 35N(3.57KGF) MAX

EXTRACTION FORCE: 10~35N(1.02~3.57KGF) MIN

DURABILITY: 1500 CYCLES EXTRACTION FORCE: 10~35N

5000 CYCLES MIN

5000 CYCLES EXTRACTION FORCE: 3~35N

3. ENVIRONMENTAL:

OPERATING TEMPERATURE: -55°C+85°C

4. Contact finish:

01: Selective Gold Flash

02: Selective Gold 3U"

03: Selective Gold 5U"

04: Selective Gold 15U"

05: Selective Gold 30U"

深圳市精拓金电子有限公司

产品图
PRODUCT CHART DWG

公差一览表

公差一览表		单位		制图		制图料号	
TOLERANCE	UNLESS OTHERWISE	UNITS	MM	DRAWING	Z-Y-B	PRODUCT PART NO.	PRODUCT PART NO.
X	±0.15	X	±5°	审核		产品名称	USB AP 双层直插17.0MM弯脚
X	±0.10	X	±2°	制图		PRODUCT NO.	
XX	±0.05	XX	±1°	核准		角法	
XXX	±0.03	XXX	±0.5°	APPD		版本	AD
DATE	2012.06.10	DATE				VER	

MAPX

MODIFICATION

DATE