



Pin NUMBER	SIGNAL NAME
1	VBUS
2	D-
3	D+
4	GND
5	StDA_SSRR-
6	StDA_SSRR+
7	GND_DRAIN
8	StDA_SSTX-
9	StDA_SSTX+
Shell	Shield

NOTES:

1. MATERIAL:
 1.1 HOUSING: HIGH TEMPERATURE THERAL PLASTIC.
 1.2 SPRING CONTACT: COPPER ALLOY.
 1.3 FLAT CONTACT: COPPER ALLOY
 1.4 SHELL : COPPER ALLOY.
 1.5 COVER: HIGH TEMPERATURE THERAL PLASTIC.
2. FINISH:
 2.1 CONTACT: (SEE P/N.), [50m"] MIN. NICKEL UNDERPLATING OVER ALL.
 2.2 SHELL: [50m"] MIN. SOLDERABILITY NICKEL UNDERPLATING OVER ALL.

MAPX	MODIFICATION	DATE

ITEM	PART NAME	Material	Q'TY	REMARK
1	Shell	C2680	1	T=0.3
2	4Pin Contact	C5191	4	T=0.25 Plating Gld/Tin
3	5Pin Contact	C2680	5	T=0.25 Plating Gld/Tin
4	Housing	LCP+30%GF	1	Blue UL94V-0
5	COVER	LCP+30%GF	1	Blue UL94V-0

公差一览表
 TOLERANCE UNLESS OTHERWISE SPECIFIED

公差	范围	其他	公差
X	±0.35	X	±5°
X	±0.30	X	±2°
XX	±0.20	XX	±1°
XXX	±0.10	XXX	±0.5°

产品图
 PRODUCT CHART DWG
 深圳市精拓金电子有限公司

单位	制图	制图料号	产品名称	角法	版本
MM	GAVIN		USB 3.0, A TYPE, 直插壳连接器.		AD
比例	审核				
1:1	郭治富				
日期	核准				
2015-04-23	黄国荣				