


MAPX	MODIFICATION	DATE
------	--------------	------

NOTE:  
 1. Material:  
 Housing: Thermoplastics (U94V-0(ROHS-HP))  
 Contact: Phosphor Bronze C5191-2H/C2680-2H, T=0.25mm  
 Shell: COPPER ALLOY T=0.30mm  
 2. FINISH:  
 Contact: 15u" Gold Plated on Contact Area,  
 80u" Min. Tin Plated on Solder Area  
 50u" Min. Nickel Underplating Over All.  
 Shell: 50u" Min Nickel Underplating Over All.  
 3. Specification:  
 3.1: Rating:  
 3.2: Rated voltage 500V AC/DC. Rated current: 2 A Max.  
 3.2: Electrical:  
 Insulation Resistance(EIA-364-21):  
 1000MΩ Min. at 500V/DC for 1Minute.  
 Contact Resistance(EIA-364-22):  
 30 mΩ Max. at 20mV Max, 50mA  
 Dielectric Withstanding Voltage(EIA-364-20):  
 No discharge, Flashover or breakdown at 500V/AC 1Minute  
 4. Plug extraction force shall be between 1.0kgf and 2.00kgf  
 5. Contact finish:  
 01: Selective Gold Flash  
 02: Selective Gold 3U"  
 03: Selective Gold 5U"  
 04: Selective Gold 15U"  
 05: Selective Gold 30U"



RECOMMENDED PCB LAYOUT  
 GENERAL TOLERANCES: ±0.05

# 深圳市精拓金电子有限公司

产品图  
 PRODUCT CHART DMC

公差一览表  
 TOLERANCE UNLESS OTHERWISE:

X.	±0.25	X.	±5.°
.X	±0.20	.X	±2.°
.XX	±0.15	.XX	±1.°
.XXX	±0.10	.XXX	±0.5°

单位 UNITS	MM	制图 DRAWING	Z-Y-B	制料号 PRODUCT PART NO.	
比例 SCALE	1:1	审核 CHKD		产品名称 PRODUCT NO.	AF10.0(侧插短体三直脚有边成品 (加高型))
日期 DATE	2014.02.20	核准 APPD		角法 VIEW	版本 VER
					A0