



PCB HOLES(THE PATTERN SIDE) t=1.6mm
NOTE: GENERAL TOLERANCE: ±0.1mm

NOTES:
1. HOUSING: SEE NOTES,
TERMINAL: SEE NOTES,
SHELL: SEE NOTES.

SPECIFICATION:
1. ELECTRICAL CHARACTERISTIC:
CONTACT RESISTANCE: 30MΩ MAX
DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1MIN
INSULATION RESISTANCE: 1000MΩ MIN

2. MECHANICAL CHARACTERISTIC:
INSERTION FORCE: 35N(3.57KGF) MAX
EXTRACTION FORCE: 10~35N(1.02~3.57KGF) MIN
DURABILITY: 1500 CYCLES EXTRACTION FORCE: 10~35N
5000 CYCLES MIN
5000 CYCLES EXTRACTION FORCE: 3~35N

3. ENVIRONMENTAL:
OPERATING TEMPERATURE: -55°C+85°C

4. Contact finish:
01: Selective Gold Flash
02: Selective Gold 3U"
03: Selective Gold 5U"
04: Selective Gold 15U"
05: Selective Gold 30U"

深圳市精拓金电子有限公司

产品图
PRODUCT CHART DWG
公差一览表
TOLERANCE TABLE OTHERWISE

公差一览表 TOLERANCE TABLE OTHERWISE		单位 UNITS	MM	制图 DRAWING	Z-Y-B	制图料号 PRODUCT DRAW NO.	
X.	±0.25	X.	±5.°	审核 CHECK		产品名称 PRODUCT NO.	USB A/F /90°/DIP/10.0mm
.X	±0.20	.X	±2.°	日期 DATE	2015.02.04	角法 VIEW	版本 VER
.XX	±0.15	.XX	±1.°	核准 APPD			A0
.XXX	±0.10	.XXX	±0.5°				

MAPX	MODIFICATION	DATE