



产品编号 : [1722563103](#)

Product Description : Ultra-Fit Tangless Receptacle Housing, 3.50mm Pitch, Single Row, 3 Circuits, Black, Glow-Wire Capable

系列号 : 172256

状态 : Active

Product Category : Connector Housings



文件和资源

图纸

[图纸 1722563103_sd.pdf](#)

[包装设计图 1723230004-000.pdf](#)

3D 模型和设计文件

[3D模型 1722563103_stp.zip](#)

规格

[应用规格 1723230003-000.pdf](#)

[产品规格 1723230001-TS-000.pdf](#)

[产品规格 1723231000-PS-CH-000.pdf](#)

[产品规格 1723231000-PS-ES-000.pdf](#)

[产品规格 1723231000-PS-JP-000.pdf](#)

[产品规格 1723231000-PS-SK-000.pdf](#)

[产品规格 PS-172323-0001-001.pdf](#)

产物环境合规

合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

[多部分产品合规性声明](#)

- Eu RoHS

- REACH SVHC

- Low-Halogen

多部分行业合规性文件

- IPC 1752A Class C

- IPC 1752A Class D

- Molex Product Compliance Declaration

- IEC-62474

- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	活动
类别	Connector Housings
系列	172256
说明	Ultra-Fit Tangless Receptacle Housing, 3.50mm Pitch, Single Row, 3 Circuits, Black, Glow-Wire Capable
应用	Power, Wire-to-Board
产品系列	Ultra-Fit Power Connectors
产品名称	Ultra-Fit
UPC	191130133819

物理

电路数（最多）	3
颜色-树脂	黑色
性别	Receptacle
符合灼热丝规范	是
插接极性	是
锁定插接部位	是
材料 - 树脂	Nylon
净重	1.253/g
行数	1
包装形式	Bag
面板安装式	否

间距 - 插配接口	3.50mm
间距 - 终端界面	3.50mm
有极性的插配件	是
运行温度范围	-40° to +105° C

可配插/可连接使用的产品

可配插部件

描述	产品编号
Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 3 Circuits, with Kinked Pins, Tin (Sn), Glow-Wire Capable, Black	<u>1722861103</u>
Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 3 Circuits, with Kinked Pins, 0.38µm Gold (Au) Plating, Glow-Wire Capable, Black	<u>1722861203</u>
Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 3 Circuits, with Kinked Pins, 0.76µm Gold (Au) Plating, Glow-Wire Capable, Black	<u>1722861303</u>
Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 3 Circuits, with Solder Clips, Tin (Sn), Glow-Wire Capable, Black	<u>1722871103</u>
Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 3 Circuits, with Solder Clips, 0.38µm Gold (Au) Plating, Glow-Wire Capable, Black	<u>1722871203</u>
Ultra-Fit Vertical Header, 3.50mm Pitch, Single Row, 3 Circuits, with Solder Clips, 0.76µm Gold (Au) Plating, Glow-Wire Capable, Black	<u>1722871303</u>
Ultra-Fit Right-Angle Header with Solder Nail, 3.50mm Pitch, Single Row, 3 Circuits, Tin (Sn) Plating, Black, Glow-Wire Capable	<u>1723103103</u>
Ultra-Fit Right-Angle Header with Solder Nail, 3.50mm Pitch, Single Row, 3 Circuits, 0.38µm Gold (Au) Plating, Black, Glow-Wire Capable	<u>1723103203</u>

Ultra-Fit Right-Angle Header with Solder Nail, 3.50mm Pitch, Single Row, 3 Circuits, 0.76 μ m Gold (Au) Plating, Black, Glow-Wire Capable	<u>1723103303</u>
Ultra-Fit Plug Housing, 3.50mm Pitch, Single Row, 3 Circuits, Black, Glow-Wire Capable	<u>2025693003</u>
Ultra-Fit Plug Housing, 3.50mm Pitch, Single Row, 3 Circuits, Panel Mount, Black, Glow-Wire Capable	<u>2025693103</u>

可连接使用部件

描述	产品编号
Ultra-Fit Tangless Crimp Terminal, Female, 0.38 μ m Gold (Au) Plating, 16-18 AWG	<u>/content/molex/molex-dot-com/cn/zh/products/product-page.html/1722536011.html</u>
Ultra-Fit Tangless Crimp Terminal, Female, 0.38 μ m Gold (Au) Plating, 20-22 AWG	<u>/content/molex/molex-dot-com/cn/zh/products/product-page.html/1722536111.html</u>
Ultra-Fit Tangless Crimp Terminal, Female, 0.76 μ m Gold (Au) Plating, 16-18 AWG	<u>/content/molex/molex-dot-com/cn/zh/products/product-page.html/1722536012.html</u>
Ultra-Fit Tangless Crimp Terminal, Female, 0.76 μ m Gold (Au) Plating, 20-22 AWG	<u>/content/molex/molex-dot-com/cn/zh/products/product-page.html/1722536112.html</u>
Ultra-Fit Tangless Crimp Terminal, Female, Tin (Sn) Plating, 16-18 AWG	<u>/content/molex/molex-dot-com/cn/zh/products/product-page.html/1722537023.html</u>
Ultra-Fit Tangless Crimp Terminal, Female, Tin (Sn) Plating, 20-22 AWG	<u>/content/molex/molex-dot-com/cn/zh/products/product-page.html/1722537123.html</u>
Pre-Crimped Lead Ultra-Fit Tangless-Female-to-Ultra-Fit Tangless Female, Tin (Sn) Plating, 150.00mm Length, 16 AWG, Black	<u>/content/molex/molex-dot-com/cn/zh/products/product-page.html/797582141.html</u>
Pre-Crimped Lead Ultra-Fit Tangless-Female-to-Ultra-Fit Tangless Female, Tin (Sn) Plating, 300.00mm Length, 16 AWG, Black	<u>/content/molex/molex-dot-com/cn/zh/products/product-page.html/797582142.html</u>
Ultra-Fit Tangless Terminal Position Assurance (TPA), 3.50mm Pitch, 3 Circuits, Natural	<u>/content/molex/molex-dot-com/cn/zh/products/product-page.html/1722644003.html</u>

This document was generated on Oct 18, 2023