



PCB HOLES(TOP VIEW)
GENERAL TOLERAMCE:±0.1mm

NOTES技术要求:

- 1.ELECTRICAL CHARACTERS 电气特性:
 1-1.RATING 额定值: DC 30V 0.5A;
 1-2.CONTATCT RESISTANCE 接触电阻:≤30mΩ;
 1-3.INSULATION RESISTANCE 绝缘电阻:≥100MΩ DC 500V;
 1-4.WITHSTANDING VOLTAGE 耐受电压:AC 500V 1min;
 1-5.LIFE 寿命:5,000 CYCLES;
 2.MECHANICAL CHARACTERISTICS 机械特性:
 2-1.INSERTION&EXTRACTION FORCE 插入和拔出力:3~30N
 2-2.OPERATING TEMPERATURE 工作温度:-30°C~+70°C;

No.	PART NAME	TER'NO.	Q'TY	MATERIAL	REMARK
⑤	COVER		1	PC	CLEAR
④	PIN	3	1	BRASS	Ag PLATED
③	BREAK TERMINAL	2	1	BRASS	Ag PLATED
②	TIP SPRING	1	1	BRONZE	Ag PLATED
①	HOUSING		1	PA66	BLACK

DSND	SCALE: N/A	MODEL TYPE: DC POWER JACK	
DWN	VIEW:	PART NO.: DC-039-2.5A	
CHKD	UNIT: mm/in	DWG NO.:	
APPD	SIZE: A4		
	WEIGHT	SHEET	REVISIC
		1/1	A0



XKB INDUSTRIAL PRECISION CO., LIMITED

广东星坤科技股份有限公司

Δx	日期
Δx	日期
Δx	日期
MARK	DESCRIPTION

文件工程章

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES

www.helloxkb.com www.helloxkb.cn www.xk-dg.cn