



Specifications:
 Voltage rating:30V AC/DC
 Current rating:0.5A AC/DC
 Withstanding voltage:500V AC/minute
 Temperature range:-40°~+55℃
 Insulation resistance:≥100MΩ
 Contact resistance:≤30mΩ
 After environmental testing:≤20mΩ
 Operating Life(Cycles):5000
 Mating Force:3-20N

PIN	PJ-313D-B-SMT
Schematic	

	MATERIAL	PLATING
terminal 1	Phosphor Bronze	ag
terminal 2	Phosphor Bronze	ag
terminal 3	Phosphor Bronze	ag
plastic	PA	

广东星坤科技股份有限公司

Δx	日期
Δx	日期
Δx	日期
MARK	DESCRIPTION

文件工程章

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
				ANGULAR ±5°
				L ≤ 4 ±0.2
				4 < L ≤ 16 ±0.3
				16 < L ≤ 63 ±0.4
				L > 63 ±0.5



DSND	SCALE: N/A
DWN	VIEW:
CHKD	UNIT: mm/in
APPD	SIZE: A4

MODEL TYPE: 3.5 PHONE JACK
PART NO.: PJ-308X-SMT
DWG NO.:
WEIGHT
SHEET 1/1
REVISIC A0

XKB INDUSTRIAL PRECISION CO., LIMITED

www.helloxkb.com www.helloxkb.cn www.xk-dg.cn