



Specifications:

规格:  
 Current rating:3A AC/DC  
 额定电流: 3A AC/DC  
 Voltage rating:250V AC  
 额定电压: 250V AC  
 Withstanding voltage:500V AC/MIN  
 耐受电压: ≥500V AC/分钟  
 Temperature range:-55℃-+105℃  
 温度范围: -55℃-+105℃  
 Insulation resistance:1000MΩMIN  
 绝缘电阻: ≥1000MΩ  
 Contact resistance:30mΩMAN  
 接触电阻:≤30mΩ  
 Material And FINISHED:  
 材料和成本:  
 INSULATOR:PBT UL 94V-0  
 绝缘体: PBT UL 94V-0  
 SHELL: SPCC-SD Plated Ni / Au / Sn  
 外壳: 铁合金 镀镍/金/锡  
 CONTACT MATERIAL:COPPER ALLOY  
 触点材料: 铜合金

X03 XX WT X X X  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series NO.
- ② Row No.Pin No:XX-09;15;25;37
- ③ Welding Board Angle :W-Male
- ④ T:Tradutional
- ⑤ Planting Category:1:1U' ;2:2U' ;3:3U' ;4:5U' ;5:15U' 6:30U' ;7:AuSn
- ⑥ B:Black W:White BL:Blue Y:Yellow G:Green R:Red
- ⑦ 1:TYPE-1; 2:TYPE-2; 3:TYPE-3; 4:TYPE-4; 6:TYPE-6

NO.OF CONTACT	A	B	C
09	30.81	24.99	16.92
15	39.14	33.32	25.25
25	53.04	47.04	38.96
37	69.32	63.50	55.42

柳合方式	TYPE-1:柳合	TYPE-6:直柳锁	TYPE-3:叉锁	TYPE-2:柳合锁螺丝
图式				

DSND		SCALE: N/A	MODEL TYPE: D-USB
DWN		VIEW:	PART NO.: X03XXWTXXX
CHKD		UNIT: mm/in	DWG NO.: X-X03XXWTXXX
APPD		SIZE: A4	WEIGHT
XKB INDUSTRIAL PRECISION CO.,LIMITED			SHEET 1/1
			REVISION A0

广东星坤科技股份有限公司

MARK	DESCRIPTION	DATE	REVISED	APPROVED
Δx				
Δx				
Δx				

文件工程章

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
				ANGLAR ±5°
				L≤ 4 ±0.2
				4<L≤ 16 ±0.3
				16<L≤ 63 ±0.4
				L> 63 ±0.5

