



MATING HEIGHT	PLUG	SOCKET
4.0	1.0	3.0
4.5	1.0	3.5
5.0	1.0	4.0
5.5	1.0	4.5
6.0	2.0	4.0
6.5	2.0	4.5



No. of contacts	Dimensions					No. of contacts	Dimensions				
	A	B	C	D	E		A	B	C	D	E
4	3.50	0.80	1.80	2.60	4.00	54	23.50	20.80	21.80	22.60	22.60
6	4.30	1.60	2.60	3.40	4.00	56	24.30	21.60	22.60	23.40	23.40
8	5.10	2.40	3.40	4.20	4.00	58	25.10	22.40	23.40	24.20	24.20
10	5.90	3.20	4.20	5.00	4.00	60	25.90	23.20	24.20	25.00	25.00
12	6.70	4.00	5.00	5.80	4.00	62	26.70	24.00	25.00	25.80	25.80
14	7.50	4.80	5.80	6.60	4.00	64	27.50	24.80	25.80	26.60	26.60
16	8.30	5.60	6.60	7.40	4.00	66	28.30	25.60	26.60	27.40	27.40
18	9.10	6.40	7.40	8.20	4.00	68	29.10	26.40	27.40	28.20	28.20
20	9.90	7.20	8.20	9.00	4.00	70	29.90	27.20	28.20	29.00	29.00
22	10.70	8.00	9.00	9.80	4.00	72	30.70	28.00	29.00	29.80	29.80
24	11.50	8.80	9.80	10.60	4.00	74	31.50	28.80	29.80	30.60	30.60
26	12.30	9.60	10.60	11.40	4.00	76	32.30	29.60	30.60	31.40	31.40
28	13.10	10.40	11.40	12.20	4.00	78	33.10	30.40	31.40	32.20	32.20
30	13.90	11.20	12.20	13.00	4.00	80	33.90	31.20	32.20	33.00	33.00
32	14.70	12.00	13.00	13.80	4.00	82	34.70	32.00	33.00	33.80	33.80
34	15.50	12.80	13.80	14.60	4.00	84	35.50	32.80	33.80	34.60	34.60
36	16.30	13.60	14.60	15.40	4.00	86	36.30	33.60	34.60	35.40	35.40
38	17.10	14.40	15.40	16.20	4.00	88	37.10	34.40	35.40	36.20	36.20
40	17.90	15.20	16.20	17.00	4.00	90	37.90	35.20	36.20	37.00	37.00
42	18.70	16.00	17.00	17.80	4.00	92	38.70	36.00	37.00	37.80	37.80
44	19.50	16.80	17.80	18.60	4.00	94	39.50	36.80	37.80	38.60	38.60
46	20.30	17.60	18.60	19.40	4.00	96	40.30	37.60	38.60	39.40	39.40
48	21.10	18.40	19.40	20.20	4.00	98	41.10	38.40	39.40	40.20	40.20
50	21.90	19.20	20.20	21.00	4.00	100	41.90	39.20	40.20	41.00	41.00

Specifications:
 规格:
 Voltage rating:200V AC/DC
 额定电压: 200V AC/DC
 Current rating:1A AC/DC
 额定电流: 1A AC/DC
 Withstanding voltage:500V AC/minute
 耐受电压: 500V AC/ 分钟
 Temperature range:-40 -+105
 温度范围: -40 -+105
 Insulation resistance:≥1000MΩ
 绝缘电阻: ≥1000MΩ
 Contact resistance:≤20mΩ
 接触电阻: ≤20mΩ
 After environmental testing:≤40mΩ
 环境测试后: ≤40兆欧

X0812 W V S-XX X S- 9T V01
 1. Series No
 2. Category:W-WAFER
 3. Welding Board Angle:V-Straight 180°
 4. Welding Way:S-SMT
 5. Row No-Pin No:XX-04P-100P
 6. Height:A=1.0mm;B=2.0mm
 7. Special No:S-With positioning Column
 8. Material:9T-PA9T UL94V-0 Black
 9. Plating:V01-Gold Flash

广东星坤科技股份有限公司

△X	日期
△X	日期
△X	日期
MARK	DESCRIPTION

文件工程章

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
ANGLAR				±5°
L ≤ 4				±0.2
4 < L ≤ 16				±0.3
16 < L ≤ 63				±0.4
L > 63				±0.5



DSND	SCALE: N/A
DWN	VIEW:
CHKD	UNIT: mm/in
APPD	SIZE: A4

MODEL TYPE: 0.8mm BTB Style connector		
PART NO.: X0812WVS-XXS-9TV01		
DWG NO.: X-X0812WVS-XXS-9TV01		
WEIGHT	SHEET	REVISION
	1/1	A0