



Specifications:

规格:

Voltage rating: 50V AC/DC

额定电压: 50V AC/DC

Current rating: 0.8A AC/DC

额定电流: 0.8A AC/DC

Withstanding voltage: 250V AC/minute

耐受电压: 250V AC/分钟

Temperature

range: -25°C +85°C

温度范围: -25°C +85°C

X1004 W V S-2xXX-9TV01

- ①
- ②
- ③
- ④
- ⑤
- ⑥

- ① Series No.
- ② Category: W-WAFER
- ③ Wedding Board Angle: V-Stringht 180°
- ④ Welding way : S-SMT
- ⑤ Row No. Pin No.: 2xXX Single Row;
- ⑥ Plug the Pin & Special No.: L-With Lock
Material: 9T-PA9T 94V-0

PIN	DIM A	DIM B	DIM C	DIM D
2X10P	9.00	12.30	10.45	11.25
2X15P	14.00	17.30	15.45	16.25
2X20P	19.00	22.30	20.45	21.25
2X25P	24.00	27.30	25.45	26.25

Autodesk

Autodesk

广东星坤科技股份有限公司

生效 MARK 日期 DESCRIPTION

文件工程章

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE:
				XKB ANGLAR ±5°	DWN	DATE	VIEW:	PART NO.:
				L ≤ 4 ±0.2	CHKD	DATE	UNIT: mm/in	2.54 mm Crimp Style Connectors
				4 < L ≤ 16 ±0.3	APPD	DATE	SIZE: A4	DWG NO.:
				16 < L ≤ 63 ±0.4				X1004WVS-2xXX-9TV01
				L > 63 ±0.5				WEIGHT SHEET REVISION
								1.0g 1/1 A0