



■ Specifications :

- Voltage rating: 200V AC / DC
- Current rating: 1A AC / DC
- Withstanding voltage: 500V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥100MΩ
- Contact resistance: ≤40mΩ
- After environmental testing : ≤80mΩ

X1255 H-XX A-N0 XX
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Category : H-HSG
- ③ Row No.-Pin No.: XX-04P~06P
- ④ Plug the Pin & Special N0:A-Double Salient
- ⑤ Material : N0-PA66 94V-0
- ⑥ Whether containing halogen:HF-Halogen free

| Poles | Dimension □ mm □ | | |
|-------|------------------|-------|-------|
| | A | B | C |
| 04 | 3.75 | 8.60 | 6.40 |
| 05 | 5.00 | 9.85 | 7.65 |
| 06 | 6.25 | 11.10 | 8.90 |
| 07 | 7.50 | 12.35 | 10.15 |

| | | | |
|-----------------|-------------------------------|-----------------------|-----------------------|
| X1255H-XXA-N0HF | PA66 UL 94V-0 Halogen Free | X1255T | X1255W |
| X1255H-XXA-N0 | PA66 UL 94V-0 | | |
| PART NO | Material | Suitable XKB Terminal | Suitable XKB Terminal |

| | | | | | | | | | | | | |
|---|-------------|------|---------|----------|-------------|------------------------|---------------------------------------|--|------|-------------|--------------------------------|----------|
| | | | | | ANGLAR | ±5° | DSND | | DATE | SCALE: N/A | MODEL TYPE: X1255H-XXA-N0XX | |
| ΔX | | | | | L ≤ 4 | ±0.2 | DWN | | DATE | VIEW: | PART NO.: | |
| ΔX | | | | | 4 < L ≤ 16 | ±0.3 | CHKD | | DATE | UNIT: mm/in | 1.25mm Crimp Style Connectors | |
| ΔX | | | | | 16 < L ≤ 63 | ±0.4 | APPD | | DATE | SIZE: A4 | DWG NO.: | |
| MARK | DESCRIPTION | DATE | REVISED | APPROVED | L > 63 | ±0.5 | | | | | | |
| | | | | | | UNSPECIFIED TOLERANCES | XKB INDUSTRIAL PRECISION CO., LIMITED | | | WEIGHT | SHEET | REVISION |
| www.xk-dg.cn www.helloxkb.com www.helloxkb.cn | | | | | | | | | | 1.0g | 1/1 | A0 |