



**Specifications:**

规格:

**Voltage rating:**250V AC/DC

额定电压: 250V AC/DC

**Current rating:**1A AC/DC

额定电流: 1A AC/DC

**Withstanding voltage:**500V AC/minute

耐受电压: 500V AC/分钟

**Temperature range:**-40 °C-+105 °C

温度范围: -40°C-+105°C

**Insulation resistance:**≥1000MΩ

绝缘电阻: ≥1000MΩ

**Contact resistance:**≤20mΩ

接触电阻: ≤20mΩ

X1270 W V S -2xXX B -6T V01

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

1. Series No
2. Category:W-WAFER
3. Welding Board Angle:V-Stright Angle 180°
4. Welding Way:S-SMT
5. Row No-Pin No:2xXX-2x05P~2x30P
6. B:Contains gaps
7. Material:6T:Nylon-6T UL94V-0
8. Plating Category: V01-All Gold Flash

NUMBER OF POSITIONS	DIMENSION		
	A	B	C
10	5.08	11.25	12.65
14	7.62	13.79	15.19
16	8.89	15.06	16.46
20	11.43	17.60	19.00
26	15.24	21.41	22.81
30	17.78	23.95	25.35
34	20.32	26.49	27.89
40	24.13	30.30	31.70
50	30.48	36.65	38.05
60	36.83	43.00	44.40

X1270WVS-2xXXB-6TV01	Nylon-6T UL 94V-0	Brass	Gold Flash	X1270H
PART NO	Material	Material(Pin And Solder Tabs)	Finish(Pin And Solder Tabs)	Suitable XKB Terminal

广东星坤科技股份有限公司  
 文件工程章

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
ANGLAR				±5°
L ≤ 4				±0.2
4 < L ≤ 16				±0.3
16 < L ≤ 63				±0.4
L > 63				±0.5



DSND	SCALE: N/A	MODEL TYPE: 1.27mm BTB Style Connectors
DWN	VIEW:	PART NO.:
CHKD	UNIT: mm/in	DWG NO.:
APPD	SIZE: A4	X1270WVS-2xXXB-6TV01
XKB INDUSTRIAL PRECISION CO., LIMITED		WEIGHT SHEET REVISION 1/1 A0