



P.C.B LAYOUT

Specifications:

规格:  
 Voltage rating: 250V AC/DC  
 额定电压: 250V AC/DC  
 Current rating: 1A AC/DC  
 额定电流: 1A AC/DC  
 Withstanding voltage: 300V AC/minute  
 耐受电压: 300V AC/分钟  
 Temperature range: -40°C ~ +105°C  
 温度范围: -40°C ~ +105°C  
 Insulation resistance: ≥500MΩ  
 绝缘电阻: ≥500MΩ  
 Contact resistance: ≤20mΩ  
 接触电阻: ≤20mΩ  
 Material: PA6T UL94V-0  
 材质: PA6T UL94V-0  
 Plating Category: 1U" Gold  
 镀层: 1U" Gold  
 Wave soldering temperature: 255±5°C, 10S  
 波峰焊温度: 255±5°C, 10S

X1321 W R - 2xXX J - C40 D18  
 ① ② ③ ④ ⑤ ⑥ ⑦

1. Series No
2. Category: W-Wafer
3. Welding Board Angle: R-Strighr 90°
4. Row No. Pin No: 2xXX-2x01~2x40Pin
5. Plastic Height: J=1.0mm
6. Pin Length: C=4.0mm
7. Pin Length: D=1.8mm

X1321WR-2xXXJ-C40D18	PA6T	Brass	X1321F
PART NO	Material	Material(Pin)	Suitable XKB Female

广东星坤科技股份有限公司

Δx	日期
Δx	日期
Δx	日期
MARK	DESCRIPTION
文件	工程章

MARK	DESCRIPTION	DATE	REVISED	APPROVED	ANGLAR	±5°
					L ≤ 4	±0.2
					4 < L ≤ 16	±0.3
					16 < L ≤ 63	±0.4
					L > 63	±0.5
					UNSPECIFIED TOLERANCES	

DSND		SCALE: N/A	MODEL TYPE: 1.27mm BTB Connector
DWN		VIEW:	PART NO.: X1321WR-2xXXJ-C40D18
CHKD		UNIT: mm/in	DWG NO.: X-X1321WR-2xXXJ-C40D18
APPD		SIZE: A4	WEIGHT SHEET REVISION 1/1 A0

**XKB INDUSTRIAL PRECISION CO., LIMITED**