



P.C.B LAYOUT

Specifications:
 规格:
 Voltage rating:250V AC/DC
 额定电压: 250V AC/DC
 Current rating:1A AC/DC
 额定电流: 1A AC/DC
 Withstanding voltage:300V AC/minute
 耐受电压: 300V AC/分钟
 Temperature range:-40°C-+105°C
 温度范围: -40°C-+105°C
 Insulation resistance:≥500MΩ
 绝缘电阻: ≥500MΩ
 Contact resistance:≤20mΩ
 接触电阻: ≤20mΩ
 Material:PA6T UL94V-0
 材质: PA6T UL94V-0
 Plating Category:1U"Gold
 镀层: 1U"Gold
 Reflow soldering temperature:260±5°C, 10S
 回流焊温度: 260±5°C, 10S

X1321 W V S - 2xXX J - C40 D53
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- 1.Series No
- 2.Category:W-Wafer
- 3.Welding Board Angle:V-Strighr 180°
- 4.Welding Way:S-SMT
- 5.Row No.Pin No:2xXX-2x01~2x40Pin
- 6.Plastic Height:J=1.0mm
- 7.Pin Length:C=4.0mm
- 8.Pin Length:D=5.3mm

Poles	A(mm)
2x02~2x15	0.10
2x16~2x30	0.15
2x31~2x40	0.20
2x41~2x50	0.25

PART NO	Material	Material(Pin)	Suitable XKB Female
X1321WVS-2xXXJ-C40D53	PA6T	Brass	X1321F

DSND	SCALE: N/A	MODEL TYPE:
DWN <td>VIEW: </td> <td>1.27mm BTB Connector</td>	VIEW:	1.27mm BTB Connector
CHKD <td>UNIT: mm/in</td> <td>PART NO.:</td>	UNIT: mm/in	PART NO.:
APPD <td>SIZE: A4</td> <td>X1321WVS-2xXXJ-C40D53</td>	SIZE: A4	X1321WVS-2xXXJ-C40D53
		DWG NO.:
		X-X1321WVS-2xXXJ-C40D53
		WEIGHT
		SHEET
		REVISION
		1/1
		A0



XKB INDUSTRIAL PRECISION CO.,LIMITED

广东星坤科技股份有限公司

MARK	DESCRIPTION	DATE	REVISED	APPROVED
Δx	日期			
Δx				
Δx				
文件	工程	章		

REVISIONS

UNSPECIFIED TOLERANCES

www.helloxkb.com www.helloxkb.cn www.xk-dg.cn

ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5