



Recommended P.C.B Layout
General Tolerance±0.05

■ Specifications :

- Voltage rating: 50 V AC / DC
- Current rating: 1A AC / DC
- Withstanding voltage: 500V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥500MΩ
- Contact resistance: ≤20mΩ
- After environmental testing : ≤30mΩ

X1502 W V S-XX-XX SN

- ① Series No.
- ② Category : W-WAFER
- ③ Welding Board Angle : V-Straight 180°
- ④ Welding Way:S-SMT
- ⑤ Row No.-Pin No.: XX-02P~15P
- ⑥ Material : 9T-PA9T;6T-PA6T;LP-LCP 94V-0
- ⑦ Plating Category: Sn-Bright Tin Plating

| Poles | Dimensions(mm) | | | Poles | Dimensions(mm) | | |
|-------|----------------|-------|-------|-------|----------------|-------|-------|
| | A | B | C | | A | B | C |
| 02 | 1.50 | 6.00 | 3.60 | 09 | 12.00 | 16.50 | 14.10 |
| 03 | 3.00 | 7.50 | 5.10 | 10 | 13.50 | 18.00 | 15.60 |
| 04 | 4.50 | 9.00 | 6.60 | 11 | 15.00 | 19.50 | 17.10 |
| 05 | 6.00 | 10.50 | 8.10 | 12 | 16.50 | 21.00 | 18.60 |
| 06 | 7.50 | 12.00 | 9.60 | 13 | 18.00 | 22.50 | 20.10 |
| 07 | 9.00 | 13.50 | 11.10 | 14 | 19.50 | 24.00 | 21.60 |
| 08 | 10.50 | 15.00 | 12.60 | 15 | 21.00 | 25.50 | 23.10 |

| | | | | |
|--------------------|------------------------------|---------------|-------------|-----------------------|
| X1502WVS-XXHF-LPSW | LCP UL 94V-0 Halogen Free | | | |
| X1502WVS-XX-6TSN | PA6T UL 94V-0 | Brass | Tin-Plated | X1502H |
| X1502WVS-XX-9TSN | PA9T UL 94V-0 | | | |
| PART NO | Material | Material(pin) | Finish(pin) | Suitable XKB Terminal |

广东星坤科技股份有限公司

生效

| MARK | DESCRIPTION | DATE | REVISED | APPROVED |
|------|-------------|------|---------|----------|
| ΔX | | | | |
| ΔX | | | | |
| ΔX | | | | |

日期

REVISIONS

www.xk-dg.cn www.helloxkb.com www.helloxkb.cn

文件工程章

| | | | |
|---------------------------------------|------|-------------|---|
| DSND | DATE | SCALE: N/A | MODEL TYPE: X1502WVS-XX-9TSN |
| DWN | DATE | VIEW: | PART NO.: 1.5mm Crimp Style Connectors |
| CHKD | DATE | UNIT: mm/in | DWG NO.: |
| APPD | DATE | SIZE: A4 | |
| XKB INDUSTRIAL PRECISION CO., LIMITED | | | WEIGHT 1.0g |
| | | | SHEET 1/1 |
| | | | REVISION A0 |