


Specifications:

规格:
Voltage rating:100V AC/DC
 额定电压: 100V AC/DC
Current rating:1.5A AC/DC
 额定电流: 1.5A AC/DC
Withstanding voltage:500V AC/minute
 耐受电压: 500V AC/分钟
Temperature range:-40℃-+105℃
 温度范围: -40℃-+105℃
Insulation resistance:≥500MΩ
 绝缘电阻: ≥500MΩ
Contact resistance:≤20mΩ
 接触电阻: ≤20mΩ


X1515 W R S- 2xXX - LP SW

① ② ③ ④ ⑤ ⑥ ⑦



1. Series No
2. Category:W-Wafer
3. Welding Board Angle:R-Stright 90°
4. Welding Way:S-SMT
5. Row No.Pin No:2xXX-2x04~2x14P
6. Material:LP-LCP 94V-0 (Natural)
7. Plating:SW- Matte Tin Plated



2x04Pin / 2x05Pin With Mylar



2x04Pin
2x05Pin



Recommended PCB Layout
Tolerance:±0.05

Poles	Dimensions(mm)			
	A	B	C	D
2x04	5.25	10.30	7.40	8.95
2x05	6.75	11.80	8.90	10.45
2x06	7.25	13.30	10.40	11.95
2x07	8.75	14.80	11.90	13.45
2x08	9.25	16.30	13.40	14.95
2x09	10.75	17.80	14.90	16.45
2x10	11.25	19.30	16.40	17.95
2x11	12.75	20.80	17.90	19.45
2x12	13.25	22.30	19.40	20.95
2x13	14.75	23.80	20.90	22.45
2x14	15.25	25.30	22.40	23.95

X1515WRS-2xXX-LPSW	LCP	Phosphor Bronze	X1515H-A
PART NO	Material	Material(Pin)	Suitable XKB Housing

DSND	SCALE: N/A	MODEL TYPE: 1.5mm Crimp Style Connector
DWN	VIEW:	PART NO.: X1515WRS-2xXX-LPSW
CHKD	UNIT: mm/in	DWG NO.: X-X1515WRS-2xXX-LPSW
APPD	SIZE: A4	WEIGHT
KKB INDUSTRIAL PRECISION CO.,LIMITED		SHEET
		1/1
		REVISI
		A0

ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5
UNSPECIFIED TOLERANCES	



广东星坤科技股份有限公司
 日期
 文件工程章

REVISIONS
 www.helloxkb.com www.helloxkb.cn www.xk-dg.cn