



P . C . B LAYOUT

Specifications:
 规格:
 Voltage rating:250V AC/DC
 额定电压: 250V AC/DC
 Current rating:1A AC/DC
 额定电流: 1A AC/DC
 Withstanding voltage:500V AC/minute
 耐受电压: 500V AC/分钟
 Temperature range:-40℃+105℃
 温度范围: -40℃+105℃
 Insulation resistance: 1000MΩ min
 绝缘电阻: 1000MΩ Min
 Contact resistance:20mΩ Max
 接触电阻: 20mΩ Max

- X2001 W R - 2xXX A - 6T V01
 ① ② ③ ④ ⑤ ⑥ ⑦
- 1.Series No
 - 2.Category:W-Wafer
 - 3.Welding Board Angle:R-Stright 90°
 - 4.Row No.Pin No.:2xXX-2x03-2x32P
 - 5.Category:A-No gap
 - 6.Material:6T-Nylon 6T UL94V-0
 - 7.Plating:V01-Gold Flash

| Poles | Dimensions | | Poles | Dimensions | |
|-------|------------|-------|-------|------------|-------|
| | A | B | | A | B |
| 2x03 | 4.00 | 13.30 | 2x12 | 22.00 | 31.30 |
| 2x04 | 6.00 | 15.30 | 2x13 | 24.00 | 33.30 |
| 2x05 | 8.00 | 17.30 | 2x15 | 28.00 | 37.30 |
| 2x06 | 10.00 | 19.30 | 2x17 | 32.00 | 41.30 |
| 2x07 | 12.00 | 21.30 | 2x20 | 38.00 | 47.30 |
| 2x08 | 14.00 | 23.30 | 2x22 | 42.00 | 51.30 |
| 2x09 | 16.00 | 25.30 | 2x25 | 48.00 | 57.30 |
| 2x10 | 18.00 | 27.30 | 2x30 | 58.00 | 67.30 |
| 2x11 | 20.00 | 29.30 | 2x32 | 62.00 | 71.30 |

| | | | |
|---------------------|----------|---------------|------------------|
| X2001WR-2xXXA-6TV01 | Nylon 6T | Brass | X2001H / X2001H2 |
| PART NO | Material | Material(Pin) | Suitable XKB IDC |

广东星坤科技股份有限公司
 日期
 文件工程章

| REVISIONS | DATE | REVISED | APPROVED | DESCRIPTION |
|-----------|------|---------|----------|-------------|
| Δx | | | | |
| Δx | | | | |
| Δx | | | | |
| MARK | | | | |

| | | |
|--------------------------------------|-------------|--|
| DSND | SCALE: N/A | MODEL TYPE: 2.0mm Crimp Style Connector |
| DWN | VIEW: | PART NO.: X2001WR-2xXXA-6TV01 |
| CHKD | UNIT: mm/in | DWG NO.: X-X2001WR-2xXXA-6TV01 |
| APPD | SIZE: A4 | WEIGHT |
| XKB INDUSTRIAL PRECISION CO.,LIMITED | | SHEET |
| | | REVISION |
| | | 1/1 |
| | | A0 |