



P . C . B LAYOUT

Specifications:
 规格:
 Voltage rating:250V AC/DC
 额定电压: 250V AC/DC
 Current rating:1A AC/DC
 额定电流: 1A AC/DC
 Withstanding voltage:500V AC/minute
 耐受电压: 500V AC/分钟
 Temperature range:-40°C--+105°C
 温度范围: -40°C--+105°C
 Insulation resistance: 1000MΩ min
 绝缘电阻: 1000MΩ Min
 Contact resistance:20mΩ Max
 接触电阻: 20mΩ Max

- X2001 W V - 2xXX A - 6T V01
 ① ② ③ ④ ⑤ ⑥ ⑦
 1.Series No
 2.Category:W-Wafer
 3.Welding Board Angle:V-Straight 180°
 4.Row No.Pin No:2xXX-2x03-2x32P
 5.Category:A-No gap
 6.Material:6T-Nylon 6T UL94V-0
 7.Plating:V01-Gold Flash

Poles	Dimensions		Poles	Dimensions	
	A	B		A	B
2x03	4.00	13.30	2x12	22.00	31.30
2x04	6.00	15.30	2x13	24.00	33.30
2x05	8.00	17.30	2x15	28.00	37.30
2x06	10.00	19.30	2x17	32.00	41.30
2x07	12.00	21.30	2x20	38.00	47.30
2x08	14.00	23.30	2x22	42.00	51.30
2x09	16.00	25.30	2x25	48.00	57.30
2x10	18.00	27.30	2x30	58.00	67.30
2x11	20.00	29.30	2x32	62.00	71.30

X2001WV-2xXXA-6TV01	Nylon 6T	Brass	X2001H / X2001H2
PART NO	Material	Material(Pin)	Suitable XKB IDC

广东星坤科技股份有限公司

DATE	DATE	DATE	DATE
DATE	DATE	DATE	DATE
DATE	DATE	DATE	DATE
DATE	DATE	DATE	DATE

文件工程章

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
ANGLAR				±5°
L ≤ 4				±0.2
4 < L ≤ 16				±0.3
16 < L ≤ 63				±0.4
L > 63				±0.5

DSND
DWN
CHKD
APPD

SCALE: N/A
VIEW:

UNIT: mm/in
SIZE: A4

MODEL TYPE:
2.0mm Crimp Style Connector
PART NO.:
X2001WV-2xXXA-6TV01
DWG NO.:
X-X2001WV-2xXXA-6TV01

WEIGHT
SHEET
REVISION
1/1
A0

XKIB

XKB INDUSTRIAL PRECISION CO., LIMITED