


Specifications:

- Voltage rating: 250V AC/DC
- Current rating: 2.5-1.0A AC/DC
- Withstanding voltage: 800V AC/minute
- Temperature range: -25 °C ~ +85 °C
- Insulation resistance: $\geq 1000M\Omega$
- Contact resistance: $\leq 10m\Omega$
- After environmental testing: $\leq 20m\Omega$


X2006 T-P SN

① ② ③ ④


- ① XKB Series No.
- ② Category: T-terminal
- ③ Material: Phosphor bronze
- ④ Plating Category: SN-Bright Tin Plating
V01: All Gold Flash



Section A-A
Scale: 1:1



Section B-B
Scale: 1:1



X2006T-PV01	Phosphor bronze	AWG#22-28	1.5mm(Max)	Gold Flash	X2006H
X2006T-PSN	Phosphor bronze	AWG#22-28	1.5mm(Max)	Stamping Before Plating: 30u"Ni MIN; 70" Sn MIN	X2006H
PART NO	Material	Wire Range	Insulation O.D.	Finish	Suitable XKB Terminal

广东星坤科技股份有限公司

4X
3X
MARK

日期

DESCRIPTION

REVISIONS

www.helloxkb.com

DATE	REVISED	APPROVED

UNSPECIFIED TOLERANCES

DSND		DATE		SCALE: N/A	MODEL TYPE: X2006T-PSN
DWN		DATE		VIEW:	PART NO.:
CHKD		DATE		UNIT: mm/in	DWG NO.:
APPD		DATE		SIZE: A4	
XKB INDUSTRIAL PRECISION CO., LIMITED				WEIGHT	SHEET
				1/1	REVISION A0

文件工程章