



Specifications:

规格:

Voltage rating:100V AC/DC
 额定电压: 100V AC/DC
 Current rating:1A AC/DC
 额定电流: 1A AC/DC
 Withstanding voltage:800V AC/minute
 耐受电压: 800V AC/分钟
 Temperature range:-40℃~+85℃
 温度范围: -40℃~+85℃
 Insulation resistance:500MΩ min
 绝缘电阻: 500MΩ Min
 Contact resistance:20mΩ Max
 接触电阻: 20mΩ Max

X2011 H M - XX A - N0

① ② ③ ④ ⑤ ⑥

1. Series No
2. Category:H-HSG
3. Category:M-Male Housing
4. Row No.Pin No:XX-02~15 Pin
5. Special No:A-With Lock
6. Material:N0-PA66 UL94V-0

| Poles | Dimensions(mm) | | Poles | Dimensions(mm) | |
|-------|----------------|-------|-------|----------------|-------|
| | A | B | | A | B |
| 02 | 2.00 | 4.70 | 10 | 18.00 | 20.70 |
| 03 | 4.00 | 6.70 | 11 | 20.00 | 22.70 |
| 04 | 6.00 | 8.70 | 12 | 22.00 | 24.70 |
| 05 | 8.00 | 10.70 | 13 | 24.00 | 26.70 |
| 06 | 10.00 | 12.70 | 14 | 26.00 | 28.70 |
| 07 | 12.00 | 14.70 | 15 | 28.00 | 30.70 |
| 08 | 14.00 | 16.70 | 16 | 30.00 | 32.70 |
| 09 | 16.00 | 18.70 | | / | / |

| X2011HM-XXA-N0 | PA66 | X2011W | X2011TF |
|----------------|----------|--------------------|-----------------------|
| PART NO | Material | Suitable XKB Wafer | Suitable XKB Terminal |

广东星坤科技股份有限公司

| | |
|------|----|
| Δ建 | 日期 |
| Δ改 | 日期 |
| Δ文 | |
| MARK | |

文件工程草

| DESCRIPTION | DATE | REVISED | APPROVED | ANGLAR | ±5° |
|-------------|------|---------|----------|------------------------|------|
| | | | | L ≤ 4 | ±0.2 |
| | | | | 4 < L ≤ 16 | ±0.3 |
| | | | | 16 < L ≤ 63 | ±0.4 |
| | | | | L > 63 | ±0.5 |
| REVISIONS | | | | UNSPECIFIED TOLERANCES | |



| | | |
|---------------------------------------|-------------|--|
| DSND | SCALE: N/A | MODEL TYPE: 2.0mm Crimp Style Connector |
| DWN | VIEW: | PART NO.: X2011HM-XXA-N0 |
| CHKD | UNIT: mm/in | DWG NO.: X-X2011HM-XXA-N0 |
| APPD | SIZE: A4 | |
| KXB INDUSTRIAL PRECISION CO., LIMITED | | WEIGHT SHEET REVISION 1/1 A0 |