




4PIN以上



2PIN和3PIN




- ①系列
- ②类别: **W-WAFER**类
- ③外观形态:
V-180°
- ④成型方式:
空码-DIP
- ⑤PIN数:
单排-XX
- ⑥空PIN位置及特殊码
- ⑦材质:
NO-PA66 94V-0 N2-PA66 94V-2
- ⑧电镀类别:G"-镀金;V"-镀全金
"O1-1U" "O2-2U" "O3-3U" "O5-5U"
"10-10U" "15-15U" "30-30U" "50-50U"
SN-镀亮锡(70-120U) SN1-镀亮锡(120U*Min.)
SW-镀雾锡 HS-高温锡
- ⑨颜色:
空码-本色或普通色

Specifications:

规格:
Voltage rating:250V AC/DC
 额定电压: 250V AC/DC
Current rating: 3A AC/DC
 额定电流: 3A AC/DC
Withstanding voltage: 1500V AC/minute
 耐压电压: 1500V AC/minute
Temperature range:-25℃~+85℃
 温度范围: -25℃~+85℃
Insulation resistance:≥500MΩ
 绝缘电阻: ≥500MΩ
Contact resistance: ≤10Ω
 接触电阻: ≤10Ω
After environmental testing:≤20mΩ
 环境测试后: ≤20mΩ

Poles	Dimensions(mm)		
	A	B	C
2	7.50	5.8	2.50
3	10.00	8.3	5.00
4	12.50	10.8	7.50
5	15.00	13.3	10.00
6	17.50	15.8	12.50
7	20.00	18.3	15.00
8	22.50	20.8	17.50
9	25.00	23.3	20.00
10	27.00	25.80	22.50
11	12.50	28.30	25.00
12	15.00	30.80	27.50
13	17.50	33.30	30.00
14	20.00	35.80	32.50
15	22.50	38.30	35.00



广东星坤科技股份有限公司
 Recommend PCB Layout

生 日期
 日期

文件工程章
 REVISIONS

DATE REVISED APPROVED
 www.xkpcb.cn www.hellixkb.com www.hellixkb.com

ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5

UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWNN	DATE	VIEW:	PART NO.:
CHKD	DATE	UNIT: mm/in	2.50 mm Crimp Style Connectors
APPD	DATE	SIZE: A4	DWG NO.:
XKB INDUSTRIAL PRECISION CO., LIMITED			X2508WV-XX-N0SN
		WEIGHT	SHEET
		1.0g	1/1
		REVISION	A0