



Specifications:

规格:
 Voltage rating:600V AC/DC
 额定电压: 600V AC/DC
 Current rating:7A AC/DC
 额定电流: 7A AC/DC
 Withstanding voltage:1500V AC/minute
 耐受电压: 1500V AC/分钟
 Temperature range:-40℃-+125℃
 温度范围: -40℃-+125℃
 Insulation resistance:1000MΩ min
 绝缘电阻: 1000MΩ min
 Contact resistance:20mΩ max
 接触电阻: 20mΩ max

X4140 H F - 2xXX - N0

- ① ② ③ ④ ⑤

1. Series No
2. Category:H-Housing
3. Housing Type:F-Female Housing
4. Row No.Pin No:2xXX-2x02~2x03P
5. Material:N0-PA66 94V-0

Poles	Dimensions(mm)	
	A	B
2x02	4.14	9.80
2x03	8.28	14.00

X4140HF-2xXX-N0	PA66	X4140W	X4140HM	X4140TM
PART NO	Material	Suitable XKB Wafer	Suitable XKB Housing	Suitable XKB Terminal

DSND		SCALE: N/A	MODEL TYPE: 4.14mm Crimp Style Connector
DWN		VIEW:	PART NO.: X4140HF-2xXX-N0
CHKD		UNIT: mm/in	DWG NO.: X-X4140HF-2xXX-N0
APPD		SIZE: A4	WEIGHT SHEET REVISION
			1/1 A0



XKB INDUSTRIAL PRECISION CO., LIMITED

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
ΔX					ANGULAR ±5°
ΔX					L ≤ 4 ±0.2
ΔX					4 < L ≤ 16 ±0.3
					16 < L ≤ 63 ±0.4
					L > 63 ±0.5