



Specifications:

规格:
 Voltage rating:600V AC/DC
 额定电压: 600V AC/DC
 Current rating:7A AC/DC
 额定电流: 7A AC/DC
 Withstanding voltage:1500V AC/minute
 耐受电压: 1500V AC/分钟
 Temperature range:-40°C-+125°C
 温度范围: -40°C-+125°C
 Insulation resistance:1000MΩ min
 绝缘电阻: 1000MΩ min
 Contact resistance:20mΩ max
 接触电阻: 20mΩ max

X4140 H M - 2xXX - N0

- ①
- ②
- ③
- ④
- ⑤

- 1.Series No
- 2.Category:H-Housing
- 3.Housing Type:M-Male Housing
- 4.Row No.Pin No:2xXX-2x02~2x03P
- 5.Material:N0-PA66 94V-0

Poles	Dimensions(mm)	
	A	B
2x02	4.14	10.36
2x03	8.28	14.50

X4140HM-2xXX-N0	PA66	X4140W	X4140HF	X4140TF
PART NO	Material	Suitable XKB Wafer	Suitable XKB Housing	Suitable XKB Terminal

DSND		SCALE: N/A	MODEL TYPE: 4.14mm Crimp Style Connector
DWN		VIEW:	PART NO.: X4140HM-2xXX-N0
CHKD		UNIT: mm/in	DWG NO.: X-X4140HM-2xXX-N0
APPD		SIZE: A4	



XKB INDUSTRIAL PRECISION CO., LIMITED

WEIGHT	SHEET	REVISION
	1/1	A0

MARK	DESCRIPTION	DATE	REVISED	APPROVED	ANGLAR	±5°
ΔX					L ≤ 4	±0.2
ΔX					4 < L ≤ 16	±0.3
ΔX					16 < L ≤ 63	±0.4
					L > 63	±0.5
REVISIONS					UNSPECIFIED TOLERANCES	