



Specifications:
 规格:
 Voltage rating: 250V AC/DC
 额定电压: 250V AC/DC
 Current rating: 3A AC/DC
 额定电流: 3A AC/DC
 Withstanding voltage: 1000V AC/minute
 耐受电压: 1000V AC/分钟
 Temperature range: -40 °C - +105 °C
 温度范围: -40 °C - +105 °C
 Insulation resistance: ≥1000MΩ
 绝缘电阻: ≥1000MΩ
 Contact resistance: ≤20mΩ
 接触电阻: ≤20mΩ
 Material: PA6T UL94V-0
 材质: PA6T UL94V-0
 Plating Category: 1U"Gold
 镀层: 1U"Gold
 Wave soldering temperature: 255±5 °C, 10S
 波峰焊温度: 255±5 °C, 10S

X4611 F V - XX - C43 D28
 ① ② ③ ④ ⑤ ⑥

1. Series No.
2. Category: F-Female
3. Welding Board Angle: V-Stright 180
4. Row No -Pin No: XX-02P-40P
5. Plastic height: C=4.3mm
6. Pin Length: D=2.8mm

X4611FV-XX-C43D28	PA6T	Brass	1U"Gold	X4611W
PART NO	Material	Material(Pin)	Finish(Pin)	Suitable XKB Wafer

DSND	SCALE: N/A	MODEL TYPE: 2.00mm BTB Connectr
DWN	VIEW:	PART NO.: X4611FV-XX-C43D28
CHKD	UNIT: mm/in	DWG NO.: X-X4611FV-XX-C43D28
APPD	SIZE: A4	WEIGHT
		SHEET
		REVISIC
		1/1
		A0



XKB INDUSTRIAL PRECISION CO., LIMITED

广东星坤科技股份有限公司

文件工程章

ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5
UNSPECIFIED TOLERANCES	

www.helloxkb.com www.helloxkb.cn www.xk-dg.cn