



P.C.B LAYOUT

Specifications:
 规格:
Voltage rating:250V AC/DC
 额定电压: 250V AC/DC
Current rating:2A AC/DC
 额定电流: 2A AC/DC
Withstanding voltage:1000V AC/minute
 耐受电压: 1000V AC/分钟
Temperature range:-40°C-+105°C
 温度范围: -40°C-+105°C
Insulation resistance:≥1000MΩ
 绝缘电阻: ≥1000MΩ
Contact resistance:≤20mΩ
 接触电阻: ≤20mΩ
Material:PA6T UL94V-0
 材质: PA6T UL94V-0
Plating Category:1U"Gold
 镀层: 1U"Gold
Wave soldering temperature:255±5°C, 10S
 波峰焊温度: 255±5°C, 10S

X4621 W R - 2xXX I - C40 D28
 ① ② ③ ④ ⑤ ⑥ ⑦

- 1. Series No
- 2. Category:W-Wafer
- 3. Welding Board Angle:R-Stright 90°
- 4. Row No.Pin No:2xXX-2x01~2x40P
- 5. Plastic Height:l=2.0mm
- 6. Pin Length:C=4.0mm
- 7. Pin Length:D=2.8mm

X4621WR-2xXXI-C40D28	PA6T	Brass	X4621F
PART NO	Material	Material(Pin)	Suitable XKB Female

广东星坤科技股份有限公司

Δ#	日期					ANGLAR	±5°
Δ#						L ≤ 4	±0.2
Δ#						4 < L ≤ 16	±0.3
Δ#						16 < L ≤ 63	±0.4
MARK	DESCRIPTION	DATE	REVISED	APPROVED		L > 63	±0.5
文件工程章						UNSPECIFIED TOLERANCES	
REVISIONS						XKB INDUSTRIAL PRECISION CO., LIMITED	
www.helloxkb.com www.helloxkb.cn www.xk-dg.cn						MODEL TYPE: 2.0mm BTB Connector	
						PART NO.: X4621WR-2xXXI-C40D28	
						DWG NO.: X-X4621WR-2xXXI-C40D28	
				WEIGHT	SHEET	REVISION	
					1/1	A0	



DSND		SCALE: N/A	MODEL TYPE: 2.0mm BTB Connector
DWN		VIEW:	PART NO.: X4621WR-2xXXI-C40D28
CHKD		UNIT: mm/in	DWG NO.: X-X4621WR-2xXXI-C40D28
APPD		SIZE: A4	WEIGHT
			SHEET
			REVISION
			1/1
			A0