



Recommend PCB Layout

■ Specifications :

- Voltage rating: 250V AC / DC
- Current rating: 7A AC / DC
- Withstanding voltage: 1500V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥1000M Ω
- Contact resistance: ≤10mΩ
- After environmental testing : ≤20mΩ

X8672 W V X - XX X - N2 XX- K2
⑩ ⑪ ⑫ ⑬ ⑭ ⑮ ⑯ ⑰ ⑱ ⑲

- ⑩ Series No.
- ⑪ Category : W-wafer
- ⑫ Welding Board Angle:V-180°
- ⑬ Welding Way:Blank-DIP
- ⑭ Row No.-Pin No.:XX-Single row
- ⑮ Plug the Pin
- ⑯ Material :
N2-PA66 94V-2
- ⑰ Planting Category:V**All Gold-Plated
*01-Gold Flash
SN-Bright tin plating 70-120u"
- ⑱ Special No.:
K2-natural color
Inserted into the board 3.6mm
Terminal long 17.5mm

Poles	Dimensions (mm)		Poles	Dimensions (mm)	
	A	B		A	B
2	3.96	7.92	12	43.56	47.52
3	7.92	11.88	13	47.52	51.48
4	11.88	15.84	14	51.48	55.44
5	15.84	19.80	15	55.44	59.40
6	19.80	23.76	16	59.40	63.36
7	23.76	27.72	17	63.36	67.32
8	27.72	31.68	18	67.32	71.28
9	31.68	35.64	19	71.28	75.24
10	35.64	39.60	20	75.24	79.20
11	39.60	43.56			

PART NO	Material	Material(Pin)	Finish(Pin)	Suitable X KB Terminal	C'ty/Bag
X8672WV-XX-N2V01-K2	Nylon 66 UL 94V-2	Brass	Gold-Flash	X8672H	1,000Pcs
X8672WV-XX-N2SN-K2			Tin-Plated		

广东星坤科技股份有限公司

生效

MARK	DESCRIPTION	DATE	REVISED	APPROVED
ΔX				
ΔX				
ΔX				

日期

REVISIONS

www.xk-dg.cn www.helloxkb.com www.helloxkb.cn

ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5

UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE: X8672WV-XX-N2SN-K2
DWN	DATE	VIEW:	PART NO.: 3.96mm Crimp Style Connectors
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

文件工程章