


PCB LAYOUT

Specifications:

规格:
 Voltage rating:250V AC/DC
 额定电压: 250V AC/DC
 Current rating:2A AC/DC
 额定电流: 2A AC/DC
 Withstanding voltage:1500V AC/minute
 耐受电压: 1500V AC/分钟
 Temperature range:-25 °C-+85 °C
 温度范围: -25 °C-+85 °C
 Insulation resistance : 1000MΩ min
 绝缘电阻: 1000MΩ Min
 Contact resistance:20mΩ Max
 接触电阻: 20mΩ Max



- 1.Series No
- 2.Category:W-Wafer
- 3.Welding Board Angle:V-Stright 180°
- 4.Row No.Pin No:XX-04-08
- 5.Material:N0-Nylon66 UL94V-0
- 6.Plating:SN-Tin Plated

Poles	DIM	
	A	B
04	7.62	10.16
06	12.70	15.24
08	17.78	20.32

X9254WW-XX-N0SN	Nylon66	Tin Plated	X9254H
PART NO	Material	Material(Brass)	Suitable XKB Housing

广东星坤科技股份有限公司

审核	日期
设计	日期
MARK	DESCRIPTION

文件工程章

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES

ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5



DSND	SCALE: N/A
DWN	VIEW:
CHKD	UNIT: mm/in
APPD	SIZE: A4

MODEL TYPE: 2.54mm Crimp Style Connect		
PART NO.: X9254WW-XX-N0SN		
DWG NO.: X-X9254WW-XX-N0SN		
WEIGHT	SHEET	REVISI
	1/1	A0

XKB INDUSTRIAL PRECISION CO.,LIMITED