



Specifications:

规格:
Voltage rating:600V AC/DC
额定电压: 600V AC/DC
Current rating:9A AC/DC
额定电流: 9A AC/DC
Withstanding voltage:1500V AC/minute
耐受电压: 1500V AC/分钟
Temperature range:-25°C~+85°C
温度范围: -25°C~+85°C
Insulation resistance:≥1000MΩ
绝缘电阻: ≥100MΩ
Contact resistance:≤10mΩ
接触电阻: ≤10mΩ
After environmental testing:≤20mΩ
环境测试后: ≤20兆欧

X9357 H M -XX -XX XX XX
 ① ② ③ ④ ⑤ ⑥ ⑦

- 01 Series No.
- 02 Category:H-HSG
- 03 Welding Board Angle:M-Male housing
- 04 RowNo.-PinNo.:XX-02P~16P
- 05 Plug the Pin & special No.:
- 06 Material:N0-PA66 94V-0:N2-PA66 94V-2
- 07 Color:Blank-Natural Color

Poles	Dimensions(mm)		
	A	B	C
02	4.20	9.60	7.50
03	8.40	13.80	11.60
04	12.60	18.00	15.80
05	16.80	22.20	20.20
06	21.00	26.40	24.10

X9357HM-XX-N2	Nylon 66 94V-2	X9357TF	X9357W Or 9357H
X9357HM-XX-N0	Nylon 66 94V-0		
PART NO	Material	Suitable XKB Terminal	Suitable XKB Terminal

广东星坤科技股份有限公司

MARK	DESCRIPTION	DATE	REVISED	APPROVED
Δ*				
Δx				
Δ效				

REVISIONS	UNSPECIFIED TOLERANCES
ANGLAR ±5°	
L ≤ 4 ±0.2	
4 < L ≤ 16 ±0.3	
16 < L ≤ 63 ±0.4	
L > 63 ±0.5	



DSND	SCALE: N/A	MODEL TYPE: 4.2mm Crimp Style Connector
DWN	VIEW:	PART NO.: X9357HM-XX-N2
CHKD	UNIT: mm/in	DWG NO.: X-X9357HM-XX-N2
APPD	SIZE: A4	

文件工程章