



Specifications :

- Voltage rating: 250 V AC / DC
- Current rating: 7A AC / DC
- Withstanding voltage: 1500V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥1000M Ω
- Contact resistance: ≤10mΩ
- After environmental testing : ≤20mΩ
- salt fog: 48H

X9396 W V -XX- 46 SN
① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Category : W-WAFER
- ③ Wedding Board Angle : V-Straight 180°
- ④ Row No.Pin No.XX-02-15
- ⑤ Material:46-PA46 94V-0
- ⑥ Planting Category:SN-Bright tin plating

Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
02	3.96	7.92	09	31.68	35.64
03	7.92	11.88	10	35.64	39.60
04	11.88	15.84	11	39.60	43.56
05	15.84	19.80	12	43.56	47.52
06	19.80	23.76	13	47.52	51.48
07	23.76	27.72	14	51.48	55.44
08	27.72	31.68	15	55.44	59.40

PART NO	Material	Material(Pin)	Finish(Pin)	Suitable XKB Terminal
X9396WV-XX-46SN	Nylon 46 UL 94V-0	Brass	Tin-Plated	X9396H

Recommend PCB Layout

广东星坤科技股份有限公司

ΔX
ΔX
ΔX
MARK

日期

DESCRIPTION

REVISIONS

www.helloxkb.com www.helloxkb.cn www.xk-dg.cn

ANGULAR ±5°
L ≤ 4 ±0.2
4 < L ≤ 16 ±0.3
16 < L ≤ 63 ±0.4
L > 63 ±0.5

UNSPECIFIED TOLERANCES

XKIB

DSND		SCALE: N/A	MODEL TYPE: X9396WV-XX-46SN
DWN		VIEW:	PART NO.: 3.96mm Crimp Style Connecto
CHKD		UNIT: mm/in	DWG NO.: X9396WV-XX-46SN
APPD		SIZE: A4	
		WEIGHT	SHEET
			1/1
		REVISIC	A0

XKB INDUSTRIAL PRECISION CO., LIMITED

文件工程章