




2x07~2x32Pin 双槽



Specifications:
规格:
Voltage rating:250V AC/DC
额定电压: 250V AC/DC
Current rating:1A AC/DC
额定电流: 1A AC/DC
Withstanding voltage:500V AC/minute
耐受电压: 500V AC/分钟
Temperature range:-40℃~+105℃
温度范围: -40℃~+105℃
Insulation resistance:1000MΩ min
绝缘电阻: 1000MΩ Min
Contact resistance:20mΩ Max
接触电阻: 20mΩ Max

X9555 H3 - 2xXX X - PT V01
① ② ③ ④ ⑤ ⑥

- Series No
- Category:H3-Two piece with bow button
- Row No.Pin No:2xXX-2x03~2x32P
- Special No:Type A or Type B
Blank-Except for special Pin bits
- Material:PT-PBT UL 94V-0
- Plating:V01-Gold Flash over Nickel

Poles	Dimensions(mm)				Poles	Dimensions(mm)			
	A	B	C	D		A	B	C	D
2x03	12.32	5.08	1.90	8.02	2x13	37.72	30.48	3.80	33.42
2x04	14.86	7.62	1.9/3.8	10.56	2x15	42.80	35.56		38.50
2x05	17.40	10.16		13.10	2x17	47.88	40.64		43.58
2x06	19.94	12.70	15.64	2x18	50.42	43.18	/		
2x07	22.48	15.24	18.18	2x20	55.50	48.26	51.20		
2x08	25.02	17.78	20.72	2x22	60.58	53.34	/		
2x09	27.56	20.32	/	2x25	68.20	60.96	/		
2x10	30.10	22.86	25.80	2x30	80.90	73.66	/		
2x11	32.64	25.40	/	2x32	85.98	78.74	/		
2x12	35.18	27.94	30.88	/	/	/	/		

X9555H3-2xXX-PTV01	PBT	Brass	X9555W-A
X9555H3-2xXXX-PTV01			
PART NO	Material	Material(Pin)	Suitable XKB Wafer

广东星坤科技股份有限公司

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
Δ#					ANGLAR ±5°
Δx					L ≤ 4 ±0.2
Δ效					4 < L ≤ 16 ±0.3
					16 < L ≤ 63 ±0.4
					L > 63 ±0.5



DSND	SCALE: N/A	MODEL TYPE: 2.54mm Crimp Style Connector
DWN	VIEW:	PART NO.: X9555H3-2xXX-PTV01
CHKD	UNIT: mm/in	DWG NO.: X-X9555H3-2xXX-PTV01
APPD	SIZE: A4	WEIGHT SHEET REVISION 1/1 A0

XKB INDUSTRIAL PRECISION CO., LIMITED