



Specifications:

规格:

Voltage rating:600V AC/DC

额定电压: 600V AC/DC

Current rating:15A AC/DC

额定电流: 15A AC/DC

Withstanding voltage:5000V AC/minute

耐受电压: 5000V AC/分钟

Temperature range:-25°C-+85°C

温度范围: -25°C-+85°C

Insulation resistance:1000MΩ min

绝缘电阻: 1000MΩ Min

Contact resistance:3.5mΩ Max

接触电阻: 3.5mΩ Max

X9635 H F - 3xXX - N2

① ② ③ ④ ⑤

1.Series No

2.Category:H-HSG

3.Category:F-Female Housing

4.Row No.Pin No:3xXX-3x02~3x05P

5.Material:N0-Nylon 66 UL94V-0

N2-Nylon 66 UL94V-2

Poles	Dimensions(mm)	
	A	B
3x02	6.35	14.05
3x03	12.70	20.40
3x04	19.05	26.75
3x05	25.40	33.10

X9635HF-3xXX-N0	Nylon 66 UL94V-0	X9635HM	X9635TM
X9635HF-3xXX-N2	Nylon 66 UL94V-2		
PART NO	Material	Suitable XKB Housing	Suitable XKB Terminal

DSND		SCALE: N/A	MODEL TYPE: 6.35mm Crimp Style Connector
DWN		VIEW:	PART NO.: X9635HF-3xXX-N2
CHKD		UNIT: mm/in	DWG NO.: X-X9635HF-3xXX-N2
APPD		SIZE: A4	WEIGHT
XKB INDUSTRIAL PRECISION CO., LIMITED			SHEET
			REVISION
			1/1
			A0

ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5
UNSPECIFIED TOLERANCES	

**XKB**

广东星坤科技股份有限公司

日期

文件工程章

REVISIONS

www.helloxkb.com www.helloxkb.cn www.xk-dg.cn