



Specifications:

规格:

- Voltage rating: 600V AC/DC
- 额定电压: 600V AC/DC
- Current rating: 19A AC/DC
- 额定电流: 19A AC/DC
- Withstanding voltage: 5000V AC/minute
- 耐受电压: 5000V AC/分钟
- Temperature range: -40°C +105°C
- 温度范围: -40°C +105°C
- Insulation resistance: 1000MΩ min
- 绝缘电阻: 1000MΩ Min
- Contact resistance: 3.5mΩ Max
- 接触电阻: 3.5mΩ Max

X9635 H M - XX - N2
 ① ② ③ ④ ⑤

1. Series No
2. Category: H-HSG
3. Category: M-Male Housing
4. Row No. Pin No: XX-02~10P
5. Material: N0-Nylon 66 UL94V-0 ; N2-Nylon 66 UL94V-2 (White)

Poles	Dimensions(mm)	
	A	B
2	13.97	6.35
3	20.32	12.70
4	26.67	19.05
5	33.02	25.40
6	39.37	31.75
8	52.07	44.45
10	64.77	57.15

X9635HM-XX-N0	Nylon 66 UL94V-0	X9635W	X9635TF
X9635HM-XX-N2	Nylon 66 UL94V-2		
PART NO	Material	Suitable XKB Wafer	Suitable XKB Terminal

广东星坤科技股份有限公司

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
ΔX					ANGLAR ±5°
ΔX					L ≤ 4 ±0.2
ΔX					4 < L ≤ 16 ±0.3
					16 < L ≤ 63 ±0.4
					L > 63 ±0.5



DSND	SCALE: N/A
DWN	VIEW:
CHKD	UNIT: mm/in
APPD	SIZE: A4

MODEL TYPE: 6.35mm Crimp Style Connector
PART NO.: X9635HM-XX-N2
DWG NO.: X-X9635HM-XX-N2

文件工程章

REVISIONS	DATE	REVISIONS	DATE	REVISIONS	DATE

XKB INDUSTRIAL PRECISION CO., LIMITED

WEIGHT	SHEET	REVISION
	1/1	A0