



P.C.B board Layout

Specifications:

规格:
 Voltage rating:600V AC/DC
 额定电压: 600V AC/DC
 Current rating:15A AC/DC
 额定电流: 15A AC/DC
 Withstanding voltage:5000V AC/minute
 耐受电压: 5000V AC/分钟
 Temperature range:-55℃~+105℃
 温度范围: -55℃~+105℃
 Insulation resistance:1000MΩ min
 绝缘电阻: 1000MΩ Min
 Contact resistance:3.5mΩ Max
 接触电阻: 3.5mΩ Max

X9635 W V - XX H - N2 SN
 ① ② ③ ④ ⑤ ⑥ ⑦

1. Series No
2. Category:W-Wafer
3. Welding Board Angle:V-Stright 180°
4. Row No. Pin No:XX-02~10Pin
5. Category:H-Hollw Pin
- Material:N0-Nylon UL94V-0
N2-Nylon UL94V-2
7. Plating:SN-Bright Tin Plated

Poles	Dimensions(mm)	
	A	B
02	6.35	13.97
03	12.70	20.32
04	19.05	26.67
05	25.40	33.02
06	31.75	39.37
07	38.10	45.72
08	44.45	52.07
09	50.80	58.42
10	57.15	64.77

X9635WV-XXH-N0SN	Nylon 66 UL94V-0	Phosphor Bronze	X9635HM
X9635WV-XXH-N2SN	Nylon 66 UL94V-2		
PART NO	Material	Material(Pin)	Suitable XKB Housing

DSND	SCALE: N/A	MODEL TYPE: 6.35mm Crimp Style Connector
DWN	VIEW:	PART NO.: X9635WV-XXH-N2SN
CHKD	UNIT: mm/in	DWG NO.: X-X9635WV-XXH-N2SN
APPD	SIZE: A4	WEIGHT SHEET REVISION
XKB INDUSTRIAL PRECISION CO., LIMITED		1/1 A0

广东星坤科技股份有限公司

文件工程章

MARK	DESCRIPTION	DATE	REVISED	APPROVED	ANGLAR	±5°
ΔX					L ≤ 4	±0.2
ΔX					4 < L ≤ 16	±0.3
ΔX					16 < L ≤ 63	±0.4
					L > 63	±0.5
REVISIONS						UNSPECIFIED TOLERANCES
www.helloxkb.com www.helloxkb.cn www.xk-dg.cn						