


RECOMMENDED PCB PATTERN DIM.  
TOLERANCE : ±0.05

- A.Material:
- 1.Insulator: Hing temperature thermoplastic UL94V-0(BLACK LCP)
  - 2.Pho.Bronze: Plating,50u"MIN nickel underplated 3-8U" GOLD ON THE CONTACT AREA; 100U" TIN PLATING ON SOLDER TAIL
- B.Electrical specifications
- Voltage rating:10V AC
  - Current rating:0.5A
  - Dielectric strength:500V AC for 1 minute min
  - Insulation resistance: 1000 MΩ
  - Contact resistance:100 mΩ max
  - Operation, temperature:-25°C TO 95°C
  - Product withstanding rff low soldering 260°C for 10S
- C.Mechanical specifications:
- 3.1Durability:5000cycles

XKSIM-011B-P8-X  
A:With B:without



②	Terminal	6	COPPER ALLOY	
①	Housing	1	LCP UL 94V-0	BLACK
ITEM	PAPT NAMF	QTY	MATERIAL	FINISHING

广东星坤科技股份有限公司

ΔX	日期
ΔX	
ΔX	
MARK	DESCRIPTION

文件工程章

					ANGLAR	±5°
					L ≤ 4	±0.2
					4 < L ≤ 16	±0.3
					16 < L ≤ 63	±0.4
					L > 63	±0.5
					UNSPECIFIED TOLERANCES	



DSND		SCALE: N/A	MODEL TYPE: SIM CARD CONN		
DWN		VIEW:	PART NO.:		
CHKD		UNIT: mm/in	DWG NO.:		
APPD		SIZE: A4	XKSIM-011B-P8-X		
			WEIGHT	SHEET	REVISIO
				1/1	A0

XKB INDUSTRIAL PRECISION CO.,LIMITED