



Recommended P.C.B Layout (Top Side)

NOTE 备注:

- 1.MATERIAL 材料
- 1.1 INSULATOR 绝缘材料:LCP UL 94V-D.BLACK
- 1.2 CONTACT 端子:H65;30U" MIN NICKEL UNDER PLATED OVERALL
80uMIN Tin PLATED ON SOLDER AREA
G/F PLATED ON CONTACT AREA
- 1.3 SHELL 外壳:H65;50u" Ni PLATED OVERALL
- 2.ELECTRICAL CHARACTERISTICS 电气特性:
- 2.1 CONTACT RESISTANCE 接触电阻:100mΩ MAX
- 2.2 CONTACT CURRENT RATING 额定电流:0.5A
- 2.3 DIELECTRIC WITHSTANDING VOLTAGE 耐电压:500 V R.M.S.
- 2.4 INSULATION RESISTANCE 1000 MΩ MIN.
- 2.5 OPERATING TEMPERATURE 工作温度:-40°C~85°C

ITEM	PAPT NAMF	QTY	MATERIAL	FINISHING
③	Shell	1	BRASS	
②	Terminal	10	BRASS	
①	Housing	1	LCP UL 94V-0	BLACK

Pin No.	NAME
1	DAT2
2	CD/DAT3
3	CMD
4	VDD
5	CLK
6	VSS
7	DAT0
8	DAT1

广东星坤科技股份有限公司

ΔX	日期
生	
校	
MARK	

文件工程章

DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
				ANGULAR ±5°
				L ≤ 4 ±0.2
				4 < L ≤ 16 ±0.3
				16 < L ≤ 63 ±0.4
				L > 63 ±0.5



DSND	SCALE: N/A
DWN	VIEW:
CHKD	UNIT: mm/in
APPD	SIZE: A4

MODEL TYPE:	TF CARD CONN
PART NO.:	
DWG NO.:	XKTF-005
WEIGHT	SHEET
	1/1
REVISION	A0

XKB INDUSTRIAL PRECISION CO., LIMITED