



- NOTES:
1. Rating: 300V 10A;
 2. Insulation Withstands Voltage: AC2000V/MIN
 3. Insulation Resistance: 500MΩ or more at DC500V
 4. Using Temperature Range: -40°C/+105°C
 5. Screw Torque Value: 0.4N.m
 6. Suitable Electric Wire: 14-22AWG
 7. "★" is the important dimension;
 8. RoHS Compliance.

Total Pitch Tolerances		Nominal dimension range																					
In mm		In mm																					
0	30	53	70	90	115	150	250	350	0	30	53	70	90	115	150	200	250	0	over				
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	over			
30	53	70	90	115	150	250	350	500	30	53	70	90	115	150	200	250	320	10	all	over			
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.60	±0.70	±0.85	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
4	SOLDER PIN	ZB126B0003	P	BRASS	Tin Plated
3	SPRING COIL	ZB126C0001	P	STAINLESS STEEL	
2	SCREW	ZBST0009	P	STEEL	Zn Plated
1	HOUSING	ZB126A0XX02 ZB126A0XX03	/	PA66(V0)	02/03P

DWG	SK	DATE	14.05.09	SCALE	A4	UNITS	mm	SHEET/OF	1/1
CHK		DATE		SCALE	3:1				
APP.		DATE		NAME	ZB126V-XXP-XS(126V)				